

DECLARATION OF CONFORMITY

as it has effect in the United Kingdom



1. Unique identification code of the product type:										
FireFX Atlas : Roomheater burning solid fuel										
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):										
Atlas 2 : 732-105 EN 13240:2001/A2:2004										
3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:										
Roomheater burning solid fuel										
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):										
FireFX Spitfire Avenue Skypark Exeter EX5 2FR United Kingdom +44 (0)1392 261990 info@firefxfires.com www.firefxfires.com										
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):										
N/A										
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:										
System 3 & 4										
7. In case of the declaration of performance concerning a construction product covered by a designated standard:										
The approved laboratory RRF - No. 1625 performed the determination of the product type on the basis of type testing under system 3 and issued test report RRF - 40 20 5515										
9. Declared performance:										
Technical specification					EN 13240:2001/A2:2004					
Essential characteristics					Performance					
Thermal output					Wood		Manufactured smokeless fuel			
Nominal heat output					6.2 kW		-- kW			
Room heating output					6.2 kW		-- kW			
Water heating output					-- kW		-- kW			
Energy efficiency					82.0 %		-- %			
Emission of combustion products					CO (%)	PM (mg/Nm ³ @ 13% O ₂)	OGC	NO _x	CO (%)	PM (mg/Nm ³ @ 13% O ₂)
					0.05	8	55	85	--	--
Flue gas temperature at nominal heat output					298 °C		-- °C			
Surface temperature					Pass					
Electrical safety					Pass					
Cleanability					Pass					
Mechanical resistance (to carry a flue / chimney)					Pass					
Maximum operating pressure					-- bar					
Reaction to fire					A1					
Risk of burning fuel falling out					Pass					
Distance to combustible materials					Minimum distances					
					Side	450 mm	Mantel	-- mm		
					Rear	180 mm				
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.										
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.										
Signed for and on behalf of the manufacturer by:										
 Ian Kingscott - Group Technical Director										
Exeter - 01 September 2025										